



EUROPHALT⁺



HIGH PERFORMANCE REPAIR ASPHALT

WHAT IS EUROPHALT+?

- Europhalt+ is a granulated, high-mastic repair asphalt approved by DIN 13108-6 for multiple application.
- It is suitable for the application on roads and other areas of traffic to repair damaged areas.
- The material is easy to use with exceptional results in respect of quality and multiple application areas.
- Europhalt+ does not require any compaction after application.
- If stored in a dry location and not being exposed to direct sun, Europhalt+ has an almost unlimited shelf life.



APPLICATION AREAS

Filling of:

- potholes
- cracks
- joints
- Drops in the carriageway
- Core drill holes

Recovery of the road surface after planing, e.g. removal of old road markings and crack repair.




The first of two layers.

APPLICATION

with an asphalt heater

First, clean the surface thoroughly. Then heat it up a little bit and use the bituminous primer.



Melt the material with an asphalt heater. The processing temperature is under 160 °C.



The melted material can then be spread with a bucket or similar and leveled with a spatula.



To level the material, also other tools and equipment can be used.



Asphalt tools out of wood allow an easy processing, we also recommend the use of asphalt release agent.

or handwork with a burner



Apply the material on the damaged area and heat it up with a burner. (For optimal results, we recommend the use of the Super-Turbo-Burner).



With a laying spatula, the material can be leveled nearly until 0 mm.



The material needs to be sprinkled with bituminous grit in the hot state.



CONTACT

EUROMARK GmbH

Bottrop

Rheinbabenstraße 75

46240 Bottrop

Germany

Phone +49 2041 792-602

Fax +49 2041 792-489

info@euromark-berlack.com

www.euromark-berlack.com

EUROMARK GmbH

Heideloh

Industriegebiet Heideloh

Hasenwinkel 3

06780 Zörbig OT Großzöberitz

Germany

Phone +49 34956 249-600

Fax +49 34956 249-601

info@euromark-berlack.com

www.euromark-berlack.com

stamp / contact person